

## Inva Low Platform Lift

**Q. Do I need to have 3 phase electric supply to the lift?**

A. No. Our lift only requires a normal 240V supply.

**Q. What is the maximum travel height?**

A. The unit will serve up to 1 metre.

**Q. What size is the platform?**

A. The standard size is 1450mm x 900mm Wide but smaller widths are available.

**Q. What is the maximum load?**

A. Maximum working load is 300Kg

**Q. What guarantee do you provide?**

A. Standard 12 month parts and labour on the whole lift.

**Q. What type of controls does the unit have?**

A. Constant pressure buttons when travelling on the lift.

**Q. Can I bridge a set of steps?**

A. Yes. There is the option of adding a bridging unit to the lift.

**Q. Can I personalise my lift?**

A. Yes. We can offer the lift in different colours, key locking, automatic doors and other options.

**Q. Do you need a supporting wall?**

A. Yes. The front facing wall will need to be structural.

**Q. How long does an installation take?**

A. On average a lift would normally be completed in 1-2 days on site.

**Q. Am I able to have a lift with an open adjacent arrangement?**

A. No. The lift is only available in an open through arrangement.

**Q. Can I have glass on the lift?**

A. Yes. We can install glass infill panels on the side of the lift and on the gate.

**Q. What stops the wheelchair from rolling off?**

A. The unit has an automatic ramp which acts as a wheel stop when the lift is travelling.

**Q. Can I view a recent installation?**

A. We have many installations around the UK and it is highly probable that we can arrange a visit to a site.